


Specification

Fuses holder

cable length 200 mm
for 5 x 20 mm fuses

- *3) max 5A
- *3) copper wire and 1 x 0,5 mm² (20AWG)
- *3) AC 230 V

- *1) **packing details:**
each fuse holder must be packed in polybag with sticker
- *2) sticker print file: 6598 NS6_sticker_new.pdf



*1) Rev.1	27.05.20	with packing details
*2) Rev.2	02.06.20	new sticker
*3) Rev.3	09.02.22	new technical details

REVISED!

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

本文未经许可不得转让及翻印，不允许引用或转载其内容，违者必纠，并须赔偿损失。保留专利及试样注册的所有权。

REACH: Must be fully comply with EC 1907/2006 concerning the Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) and must not contain any of the Substances of Very High Concern (SVHC) above the specified concentrations, as defined in Article 57 and Annex XIV (including all amendments) or any of the restricted substances, as defined in Article 67 and Annex XVII (including all amendments).

VerpackG: According to the Packaging Act (VerpackG), the cumulative concentration of lead, cadmium, mercury and hexavalent chromium does not exceed 100 mg per kg.

RoHS: All Materials must be in accordance with 2011/65/EU and 2015/863/EU.

	Date	Name	Designation:
Prep.:	15.05.20	K.B	Fuses holder
Check.:			
Rev.3	09.02.22	K.B	
Approv.			

6598 NS6	Page: 1
	Page tot.: 1